

WA-2319 Specification Sheet

Rim Size:	16 X 7.5
Rim Contour:	TRA J (ISO)
Offset:	-0.07 in [-1.8 mm]
Mounting Pattern:	5 Holes on Ø5.9055 in [150.0 mm] B.C.D.
Hub Bore:	Ø4.355 in [110.6 mm]
Load Rating:	3415 lb @ 80 psi [1549.0 kg @ 5.52 bar]
Weight:	34.5 lb [15.6 kg]
Tire Size:	265/75R16
CTI Valve:	None



Hidden Hardware — 2 piece

Hutchinson Industries Inc.
 250 Ewing Street, Trenton NJ 08609
 Tel: 609.394.1010 Fax: 609.278.0526

We make it *possible*

THE INFORMATION CONTAINED IN, OR DISCLOSED BY, THIS DOCUMENT IS CONSIDERED PROPRIETARY AND CONFIDENTIAL BY HUTCHINSON. THIS DOCUMENT AND THE INFORMATION DISCLOSED HEREIN SHALL NOT BE USED, COPIED, OR CORRESPONDED IN WHOLE OR IN PART, NOR SHALL THE CONTENTS BE REVEALED IN ANY MANNER TO ANY PERSON UNLESS WRITTEN PERMISSION IS OBTAINED FROM HUTCHINSON.